

Length Overall - (LOA) 60' 11" (18.57 m) Length on Deck - (LOD) 55' 2" (16.81 m) Length at Waterline - (LWL) 49' 6" (15.09 m) Beam (Molded) - 17' 6" (5.33 m) Beam (Over Rub Rail) - 18' 0" (5.49 m) Draft (Designed Water Line - DWL) – 4' 10" (1.47 m) Displacement (DWL with Half Load) –

87,870 lb. (39,857 kg)) Ballast (Encapsulated Lead) – 6,900 lbs. (3,130 kg) Fuel - 1,880 gallons (7,117 l) Water - 500 gallons (1,893 l) Approximate Bridge Clearance

with Mast - 24' 1" (7.34 m)

CONSTRUCTION

- Hull and superstructure molds from highgrade female tooling.
- Hull construction includes use of USA-made, Cook[®] gel coat. Hand-laid Knytex (in combination with mat and Corecell[®]) above waterline; solid fiberglass lamination below waterline, with blister-resistant vinylester resins utilized on first laminates.
- Impact resistant aramid fiber/FRP reinforced stem and stern bottom areas.
- Superstructure includes Knytex[®] and mat (in combination with Corecell[®] cores) and surface mats for print-through reduction.
- Aft deck is teak. Boat and fore decks have GripTex[®] non-skid finish. Bulwark has molded plank lines with gel coat finish.
- Polyurethane formulated marine sealants used at hull-to-deck, boat deck joints and exterior fittings.
- Marine-grade plywood and foam-cored bulkheads with molded fiberglass hat section stringers.
- Interior finished with handcrafted solid cherry and veneers.

MACHINERY

- Engines: (2) Tier III John Deere^{*}, #4045AFM85, 160 bhp @ 2300 rpm with ZF Marine^{*} #280-1A gear
- Shafts: (2) Aquamet[®] 22, 2" diameter
- Shaft Seal: Tides[®] dripless
- Propellers: (2) Hung Shen^{*}, bronze, 4bladed, 31" diameter x 16.5" pitch
- Rudders: stainless with protective shoe
- Generator: 16KW Northern Lights[®] with sound shield and water/exhaust separator
- Bilge Pumps: Rule[®] (6) @ 3,700 gallons-perhour with Ultra[®] high water alarm at (2) stations

Krogen 55' Expedition Standard Specifications

- Emergency Bilge Pump: tied into the raw water intake on each engine
- Muffler: fiberglass
- Engine room intake and exhaust fans with moisture eliminators
- Steering: Teleflex^{*}, hydraulic (1-station)
- Controls: ZF Mathers Cruise Command electronic (3-station)
- Fuel Tanks: (4) aluminum with sight gauges
- Fuel Filters: Dual Racor[®] w/ vacuum gauge for main engines and generator

COMPONENTS

- Electrical Panels: 120/240-volt AC and 12/24-volt DC, with tinned wiring and circuit breakers
- Tinned wiring, throughout
- Battery Boxes: fiberglass
- Batteries: Lifeline^{*} AGM (4) 12-volt wired in series for 24V DC engine starting, (2) 12-volt wired in series for 24V DC generator starting, (16) 6-volt 300Ah wired in series for 24V DC ship service
- Battery Charger: (1) Mastervolt[®] 60 amp
- Inverter/Battery Charger: Magnum Energy 4000 watt, 105 amp charger
- Alternators: Balmar[®] 190 amp, 24-volt
- Isolation Transformers: Charles Industries[®]
- Water Piping: copper, insulated
- Dockside Water Pressure Regulators (2) Jabsco^{*}
- Pressure Water System: Headhunter Mach 5 Multistage Fresh Water Pressure Pump, 115V AC
- Water Heater: Torrid[®], 30-gallon capacity
- Water Tank: (2) stainless, 250 gallons each
- Holding Tank: fiberglass, 140-gallon capacity with SeaLand[®] macerator
- Gray Water Tank: fiberglass, 140-gallon capacity with SeaLand[®] macerator
- Holding Tank Indicator and Control Panel: SeaLand[®] TankManager[™]
- CO Detectors: Fireboy[®]-Xintex[®]
 - Fire Suppression System: Sea-Fire* FD-1150M with automatic shutdown, alarm and manual pull

EXTERIOR

- Prep, prime and paint bottom with 2 coats of Sea Hawk Epoxy Primer and 2 coats of Sea Hawk Cukote™ antifouling paint. Color Dark Blue
- Prep, prime and paint running gear with PropOne, two-coat paint scheme comprising of an anti-corrosive Primer Coat and Foul Release Coating (Clear Coat)

- Sand and prep Teak cap rail, name boards and flagstaffs and apply eight coats of varnish
- Doors: weather-tight, welded aluminum, double doors in saloon, (2) Dutch-style in pilothouse, all painted to match superstructure
- Windows: 12 mm non-opening tempered glass throughout
- Master Stateroom Hatches: (2) Lewmar with Oceanair Skyscreen and shades
- Ports: Man Ship[®], stainless with screens
- Thru-Hulls and Seacocks: bronze
- Hawse Pipes and Cleats: 316L stainless steel
- Mooring Cleats: 316L stainless steel
- Bow Eye 316L stainless steel

Aft Deck

- Cockpit with teak decking
- Transom Door with stainless steel latch
 handle and hold back
- Swim Platform: fiberglass with under mount swim ladder and (2) folding cleats
- Lazarette access hatch with ladder
- Emergency Tiller
- Side Boarding Gates: (2) with stainless steel latch handle and hold back
- Ladder: stainless steel with teak treads to boat deck
- Transom Shower: Scandvik[®] hot/cold fresh water
- Fuel Spill Prevention Boxes
- Shore Power Inlet: (2) Marinco[®], 50 amp
- Fresh water bib
- TV Inlet: Marinco*
- Fresh water bib
- Dockside Water Pressure Regulators
- Overhead LED blue/white combination lighting

Portuguese Bridge

- Wing stations with engine and thruster controls (2)
- Boarding Doors: (2) with stainless steel latch handle and hold back

Boat Deck

- Boat Deck Railings: welded 316L stainless
- Mast: aluminum, painted and hinged, with masthead, anchor and steaming lights
- Davit: Steelhead Marine ES-1200 with four function hydraulics and pedestal base
- Air Horn: Kahlenberg[®] with automatic foghorn whistle control in pilothouse
- Summer Kitchen: fiberglass cabinet with grill, sink with hot and cold water

 Propane Locker with (2) 20lb aluminum propane tanks

Bow

- Bow Railings: welded 316L stainless steel
- Bowsprit and pulpit with (2) anchor rollers
- Windlass: Maxwell[®] 3500 VWC hydraulic, with chain wheel and independent rope capstan with 400 feet of 1/2-inch HT chain and 121lb. Rocna Vulcan anchor
- Watertight Anchor Locker Deck Hatch: Freeman Marine[®]
- Shore Power Inlet: (2) Marinco^{*}, 50 amp
- TV Inlet: Marinco[®]
- Fresh Water Bib
- Salt Water Anchor Washdown: ShurFlo[®]

INTERIOR

- Overhead Lighting: i2 Systems[®] LED
- Courtesy Foot Lighting: i2 Systems[®] LED
- Wall and reading light fixtures: Imtra[®] LED
- AC receptacles, throughout
- CATV Outlets
- Cherry and Spruce floors
- Choice of UltraLeather or Ultrasuede[®] fabric, single color from KKY selection
- Sole hatches to be gasketed and have locking mechanism
- Doors: solid cherry gasketed with Mobella hardware and holdbacks
- Hanging lockers to have automatic interior light controls
- Drawers to have stainless steel slides
- CO Detectors: Fireboy[®]-Xintex[®]
- Smoke and Fire Alarms: Fireboy[®]-Xintex[®]

Saloon/Galley

- Settee: L-shaped to port, with storage below
- Table: cherry, fold-out top with hi/low base
- Valances: cherry
- Invisible sliding screen on saloon door
- Bookcase/Storage Unit: cherry with granite countertop
- Galley Sink: Elkay[®], stainless steel, double basin with Grohe faucet
- Galley Counter Tops: granite, choice of color from KKY standard selection
- Galley Appliances: stainless steel finish
- Dishwasher: GE®
- Microwave/Convection Oven: GE®
- Range/Oven: Bluestar® 24" propane
- Refrigerator Jenn-Air®
- Trash Compactor: GE®
- Wine Cooler: GE®

Pilothouse

- Compass: Ritchie[®]
- Rudder Angle Indicator: VDO[®]
- Windshield Wipers with Washers: (3) Imtra[®] Exalto
- Wheel: cherry

- Settee/Watch Berth with Cherry High-Low Table: converts to double
- Overhead Hand Rails: (2) cherry
- Overhead electronics cabinet
- Overhead Lights: i2 Systems[®] red/white combination, LED
- Electronics Console: cherry, raised wedge shaped with removable face
- Chart Drawers
- Chart Light: Imtra[®], LED
- Refrigerator/Icemaker: U-Line[®] with cherry wood insert

Master Stateroom

- Island Queen with drawer storage and pneumatic lift struts on bed platform with storage below
- Bureau with cherry wood trim mirror and model Bonn LED fixtures
- Foam mattress
- Hanging lockers
- Mirror with cherry wood trim and model
 Bonn LED fixtures
- Flooring: cherry and spruce floors
- Hatches with Oceanair Skyscreen and shade
- Overhead Lighting: dimmable LED with
 Vimar switches
- Wall lighting: (2) model Cygnus with ivory shade

Master Head

- Toilet: household size Dometic Master Flush[®] with status panel
- Shower: molded fiberglass with tempered glass door
- Counter Tops: granite, choice of color from KKY standard selection
- Fixtures: Grohe[®]
- Sink: Corian*
- Ventilation Fan: Rule 24V DC
- Vanity with cherry wood trim mirror and model Bonn LED fixtures
- Overhead Lighting: LED with Vimar switches

Guest Stateroom

- Settee that converts to double berth with drawer storage
- Desk with file drawer
- Book shelves
- Foam mattress
- Hanging locker
- Flooring: cherry and spruce floors
- Overhead Lighting: dimmable LED with Vimar switches
- Reading Light Fixtures: Imtra LED
- Washer/Dryer: GE[®]

Guest Head

 Toilet: household size Dometic Master Flush[®] with status panel

©2020 Kadey-Krogen Yachts, Inc – Revised March 2020 - Subject to change without notice

• Shower: (2) molded fiberglass with tempered glass door

- Counter Tops: granite, choice of color from KKY standard selection
- Fixtures: Grohe®
- Sink: Corian®
- Ventilation Fan: Rule 24V DC
- Vanity with cherry wood trim mirror and model Bonn LED fixtures
- Overhead Lighting: LED with Vimar switches

Machinery Space/Engine Room

- Sound Insulation: Pyrotek, Sorberflex with perforated aluminum
- Work bench with sink
- Doors/Hatches: (4) weather-tight
- Lighting: Imtra[®], LED
- Stanchion Isolators: Soundown
- Sole boards with Awlgrip non-skid paint
- Fresh water hose with nozzle

whipped blue, no eyes

• (2) Type IV Ring Buoy

• (1) Handheld Air Horn

• (1) Waste Placard

Extinguishers

(1) Oil Discharge Placard

Excursion First Aid Kit
 Kidde[®] Mariner 110 Fire

• (2) Boat Hook, telescoping

Stainless Steel Name Plate

systems orientation training

schematics and docking plan

owner's plaque

System

(1) 50-foot no-kink drinking water hose

(4) Deluxe Leather Fender Hooks with

Provide two days of boat handling and

Owner's manual with detailed system

Vessel Vanguard Yacht Management

KKY burgee, name plates, step plates and

Gallon John Deere Cool-Guard
 Gallon John Deere Break-In Oil

(contains 4)

fenders

Road"

٠

• (2) Type I Offshore Jackets

Provide Commissioning / Safety Kit:

COMMISSIONING PACKAGE ITEMS

Provide the following KKY-colored, 3/4 -inch braided dock lines:
(2) 60-foot lengths, one end whipped

red and the other end with 3-foot eye

gold and the other end with 3-foot eye

blue and the other end with 3-foot eye

• 3/8-inch x 15 feet fender lines with ends

• (1) Type II Near-Shore Buoyant Vest Sets

(4) 15" x 41" Taylor[®] Tuff End white

• (1) US Yachting Flag, 36" x 60" size

(1) Flare Kit (25mm Alert/Locate)

(1) US Coast Guard's "Rules of the

• (4) 40-foot lengths, one end whipped

• (2) 30-foot lengths, one end whipped