



Krogen 60' Open

Standard Specifications

Length Overall (LOA) - 63' 1" (19.23 m)
Length on Deck (LOD) - 60' 2" (18.34 m)
Length at Waterline (LWL) - 54' 2" (16.51 m)
Beam (Molded) - 18' 11" (5.77 m)
Beam (Over Rub Rail) - 19' 4" (5.89 m)
Draft at Design Water Line (DWL) 5' 8" (1.73 m)
Displacement (DWL with Half Load) 120,000 lbs.
(54,400 kg)
Ballast (Encapsulated Lead) - 8800 lbs. (3990 kg)
Fuel - 1,800 gal. (6,814 l)
Water - 450 gal. (1700 l)
Approximate Bridge Clearance to Top of Hard
Top - 21' 3" (6.48 m) (plus mast/antennas)
Approximate Bridge Clearance with Arch/
hardtop removed - 17' 8" (5.38 m)
(DWL to top of flybridge coaming)

CONSTRUCTION

- Hull and superstructure molds from high-grade female tooling.
- Hull construction includes use of USA-made, Cook® gel coat. Hand-laid Knytex® fiberglass construction with Corecell® closed-cell PVC sandwich core above waterline. Solid fiberglass below waterline with blister-resistant vinylester resin utilized. Aramid fiber/FRP reinforced bow and stern bottom areas.
- Superstructure includes Knytex® and mat in combination with Corecell® cores and surface mats for print-through reduction.
- Teak aft and side deck. Boat and fore decks have GripTex® non-skid finish. Bulwark has molded plank lines with gel coat finish.
- Polyurethane formulated marine sealants used at hull-to-deck, boat deck joints and exterior fittings.
- Vacuum bagged foam cored bulkheads with molded fiberglass hat section stringers.
- Interior finished with handcrafted solid cherry and veneers.

MACHINERY

- Engines: Tier III John Deere® #4045AFM85, M3 200 bhp at 2500 rpm with ZF Marine 3.000:1 ratio gear.
- Shafts: Aquamet® 22, 2" diameter.
- Shaft Seals: Tides® dripless.
- Propellers: Hung Shen®, bronze, 4-bladed, 33" diameter.
- Rudders: stainless steel with protective shoes.
- Generator: Northern Lights® 20KW with sound shield and water/exhaust separator.

- Bilge Pumps: (5) Rule®, @ 3,700 gallons-per-hour with Ultra® High Water Alarm (2 station).
- Emergency Bilge Pump: tied into the raw water intake on the main engine.
- Muffler: Centek®, fiberglass.
- Steering: Teleflex®, hydraulic (2-station).
- Controls: ZF Mathers Cruise Command (4-station).
- Fuel Tanks: (4) aluminum with sight gauges.
- Fuel Filters: Dual Racor® w/ vacuum gauge for main engines and generator.
- Engine room intake and exhaust fans with moisture eliminators.

COMPONENTS

- Electrical Panel: 110/220-volt AC and 12/24-volt DC, with circuit breakers.
- Tinned wiring, throughout.
- Battery Boxes: fiberglass.
- Batteries: Lifeline® AGM (2) 12-volt wired in series for 24V DC engine starting, (1) 12-volt 12V DC generator starting, (12) 6-volt 400Ah wired in series for 24V DC ship service.
- Inverter/Battery Charger: Mastervolt.
- Engine Battery Charger: Mastervolt 60 amp.
- Alternators with External Regulators: Balmar® 190A each.
- Isolation Boost Transformer: ANG®.
- Water Piping: copper, insulated.
- Dockside Water Pressure Regulator: (2) Jabsco®.
- Pressure Water System: Headhunter®, Mach 5 115V AC fresh water pump.
- Water Heater: Torrid®, 30-gallon.
- Water Tanks: (2) 316L stainless steel 450-gallon total capacity.
- Holding Tank: fiberglass, 140-gallon.
- CO Detectors: Fireboy®-Xintex®.
- Smoke and Fire Alarms: Fireboy®-Xintex®.
- Fire Suppression System: Sea-Fire® FD-1500M with automatic shutdown, alarm and manual pull.

EXTERIOR

- Exterior Cushions upholstered in Sunbrella Marine grade fabric and Exterior Canvas package.
- Prep, prime and paint bottom with 2 coats of Sea Hawk Epoxy Primer and 2 coats of Sea Hawk Cukote™ antifouling paint. Color: dark blue.
- Prep, prime and paint running gear with PropOne, two-coat paint scheme.
- Sand and prep flag staffs and apply eight coats of varnish.

- Doors: weather-tight, welded aluminum, (2) Dutch-style in Pilothouse, forward engine room door and aft engine room door.
- Saloon door, sliding with full glass panel.
- Windows: Windows: Fixed with tinted, tempered 12mm glass. Clear glass in forward facing pilothouse.
- Fore Deck Hatches: (2) Lewmar with Oceanair Skyscreen and shades.
- Ports: Man Ship®, stainless with screens.
- Thru-Hulls and Seacocks: bronze.
- Hawse Pipes and Cleats: 316L stainless.
- Mooring Cleats: 316L stainless steel.
- Bow Eye 316L stainless steel.
- Fuel fill spill prevention box.

Aft Deck

- Cockpit with teak decking.
- Transom Door with stainless steel latch handle and hold back.
- Swim Platform: fiberglass with under mount swim ladder and (2) folding cleats.
- Lazarette access hatch with ladder.
- Side Boarding Gates: (2) with stainless steel latch handle and hold back.
- Transom Shower: Scandvik® hot/cold fresh water.
- Fresh Water Bib.
- Shore Power Inlets: (2) Marincor®, 50 amp.
- Overhead LED blue/white combination lighting.

Portuguese Bridge

- Wing stations with engine controls and start/stop panel (2).
- Boarding Doors: (2) with stainless steel latch handle and hold back.

Flybridge/Boat Deck

- Davit: Steelhead Marine ES-1500.
- FRP summer kitchen cabinet with BBQ and propane locker.
- Boat Deck Railings: welded 316L stainless steel.
- Radar Arch: hinged, with masthead, steaming and deck lights.
- U-shaped settee Marine Grade Sunbrella.
- Horn: Kahlenberg® with automatic fog horn whistle control.
- Wheel: Edson®, stainless steel, destroyer type.
- Helm Chair: (1) Stidd Slimline Admiral.
- Compass: Ritchie®.
- Propane Locker: Trident® with (2) 20lb aluminum propane tanks.
- Tables: Teak with stainless steel pedestal.
- Wet bar with Isotherm Cruise 85 refrigerator.

Bow

- Bow Railings: welded 316L stainless steel.
- Bowsprit stainless steel with anchor roller.
- Windlass: Maxwell® 4000 VWC, hydraulic with chain wheel and independent rope capstan with 400' 1/2" HT chain and 121-lb. Rocna Vulcan anchor.
- Watertight Anchor Locker Deck Hatch: Freeman Marine®.
- Shore Power Inlet: (2) Marinc® , 50 amp.
- Fresh Water Bib.
- Salt Water Anchor Washdown: ShurFlo®.

INTERIOR

- Overhead Lighting: i2 Systems® LED with Vimar switches.
- Courtesy Foot Lighting: i2 Systems LED.
- Wall and Reading Light Fixtures: Imtra LED.
- AC receptacles, throughout.
- Cherry and Spruce floors.
- Sole hatches to be gasketed and have locking mechanism.
- Fabrics: Choice of UltraLeather® single color from KKY selection.
- Doors: Solid Cherry or solid Cherry gasketed with holdbacks.
- Hanging lockers to have automatic interior light controls.
- Drawers to have stainless steel slides.

Saloon/Galley

- Settee: UltraleatherL-shaped with storage below
- Table: Cherry, fold-out top with stainless steel high/low pedestal base.
- Sliding screen on saloon door.
- Galley Sink: Stainless steel, single basin with Grohe faucet.
- Galley Counter Tops: Silestone® Quartz - Zeus Blanco Polished.
- Below counter trash and recycling pull-out container.
- Galley Appliances: Stainless Steel Finish
 - Microwave Oven- Wolf 30".
 - Range/Oven – Wolf 30" propane.
 - Refrigerator – Subzero BI-30U/ S.

Pilothouse

- Compass: Ritchie®.
- Rudder Angle Indicator: VDO®.
- Windshield Wipers with Washers: (3) Imtra®
- Wheel: Cherry Wood.
- Settee with Cherry High-Low Table: converts to double watch berth.
- Overhead Hand Rails: (2) Cherry.
- Overhead electronics cabinet.
- Overhead Lights: i2 Systems red/white LED.
- Helm Seat: Stidd Slimline choice of color.
- Electronics Console: Cherry, raised wedge shaped with removable face.
- Chart Light: Imtra®, LED.
- Holding Tank Indicator and Control Panel: Dometic® TankManager™.

Accommodations

Standard layout includes 3 stateroom with mid-ship master king berth, VIP with queen fwd and guest stateroom to port with twin berth

Master Stateroom

- Island king berth with drawer stowage below and pneumatic lift struts on bed.
- Foam mattress.
- Bureau with drawers.
- Hanging lockers.
- Mirror with Cherry wood trim and model Bonn LED lighting.
- Flooring: Cherry and Spruce floors.
- Overhead Lighting: dimmable LED with Vimar switches.
- Wall lighting: (2) with shades.
- Desk with storage.

Master Head

- Toilet: household size Dometic Master Flush® with status panel.
- Shower: tile with tempered glass door.
- Counter top: Silestone® Quartz - Zeus Blanco Polished.
- Sinks: (2) Corian®.
- Ventilation Fan.
- Fixtures: Grohe.
- Vanity with Cherry Wood trim mirror and model LED fixtures.
- Overhead Lighting: LED with Vimar switches.

VIP Stateroom

- Island queen berth with drawer stowage below and pneumatic lift struts on bed.
- Foam mattress.
- Hanging locker.
- Mirror with Cherry Wood trim and model Bonn LED lighting.
- Flooring: Cherry and Spruce floors.
- Overhead Lighting: LED with Vimar switches.
- Wall lighting: (2) with shades.
- Hatches with Oceanair Skyscreen and shade.

VIP / Port Guest Stateroom Heads

- Toilet: household size Dometic Master Flush® with status panel.
- Showers: molded fiberglass with tempered glass door.
- Counter Tops: Silestone® Quartz - Zeus Blanco Polished.
- Sink: Corian®.
- Ventilation Fan.
- Fixtures: Grohe®.
- Vanity with Cherry Wood trim mirror and model LED fixtures.
- Overhead Lighting: LED with Vimar switches.

Companionway

- Washer/Dryer: GE®.

Port Guest Stateroom

- Choice of twin berths with storage below, or queen berth with storage below.
- Foam mattress.
- Hanging locker.
- Mirror with Cherry Wood trim.
- Flooring: Cherry and Spruce floors.
- Overhead Lighting: LED with Vimar switches.

COMMISSIONING PACKAGE ITEMS

- Provide the following KKY-colored, 3/4-inch braided dock lines:
 - (2) 60-foot lengths, custom color, one end whipped and the other end with 3-foot eye.
 - (4) 40-foot lengths, custom color, one end whipped and the other end with 3-foot eye.
 - (2) 30-foot lengths, custom color, one end whipped and the other end with 3-foot eye.
 - (4) 3/8-inch x 30 feet fender line, custom color, with ends whipped no eyes.
- Provide Commissioning Safety Kit, as follows:
 - (2) Type 1 Offshore Jackets.
 - (2) Type 11 Near-Shore Buoyant Vest Set (contains 4).
 - (2) Type IV Ring Buoy.
 - (4) 15" x 41" Taylor® Tuff End white fenders.
 - US Yachting Flag, 30" x 60" size.
 - Handheld Air Horn.
 - Flare Kit (25mm Alert/Locate).
 - US Coast Guard's "Rules of the Road".
 - Waste Placard.
 - Oil Discharge Placard.
 - Excursion First Aid Kit.
 - (5) Kidde® Mariner 110 Fire Extinguishers.
 - (2) Boat Hook, telescoping.
- (1) 50-foot no-kink drinking water hose.
- (1) Gallon John Deere Cool-Guard.
- (1) Gallon John Deere Break-In Oil.
- Provide two days of boat handling and systems orientation training.
- KKY burgee, name plates, step plates and owner's plaque.
- Owner's manual with detailed system schematics and docking plan.
- Vessel Vanguard Yacht Management System.

Engine room

- Sound Insulation: Pyrotek, Sorberflex with perforated aluminum.
- Lighting: Quick®, LED.
- Stanchion Isolators: Soundown.
- Sole boards with non-skid.
- Fresh water hose with nozzle.